



XPY-530 Integrated wireless IP camera



SD memory card slot
*(Card not included)



Ports for sensors



HD wide coverage



Integrated mobile view



Wireless connectivity



Two-way audio capability

Product overview

Our integrated wireless IP camera combines high-quality digital video with network connectivity and a powerful web server, ideal for commercial and residential applications. The images that this camera records can be sent over the internet and viewed in your web browser, giving you the peace of mind that comes from enhanced video surveillance. With advanced features like alarm sensors for emergency and fires and a motion detection function, this camera not only lets you see what's happening in real time, but also boosts your sixth sense when you aren't looking!

Advantages

- High-quality CMOS sensor delivers sharp color images.
- High-speed video processor that supports multiple network protocols for instant viewing.
- Highly-perceptive motion detector triggers snapshots and sends an instant notification directly to your email address.
- Infrared night-vision gives you 24-hour security
- Wireless connectivity supporting WEP, WPA-PSK and WPA2-PSK encryption methods.

Main features

- The camera combines a high-sensitivity 1/4 CMOS image sensor with a powerful wireless web server in order to capture clear images from anywhere, and to transmit them instantly on your local network or over the internet.
- Can be used on WiFi or wired networks.
- It uses the MJPEG hardware compression technique, which can display high-quality and real-time video transmission at 30 fps on a LAN/WAN connection.
- Digital zoom (when using the IPC monitor)
- Selectable image resolution of 1280x720 (HD) 640x480 (VGA) and 320x240 (QVGA) pixels.
- The system can be expanded at any time by adding multiple cameras.
- Two-way communication with built-in microphone and output for external speakers.
- View multiple cameras in split screen view or choose full screen in order to monitor the activity from a single camera.
- Cameras can be viewed via standard PC or Mac browsers, including Internet Explorer, Safari, Chrome and Firefox.
- Infrared LEDs for night vision up to 5 meters.
- Includes multi-level user management system, which can be configured with passwords for controlled access.
- Easy- to-use web browser controls. They also allow quick configuration changes via the Settings menu.
- Compatibility with smartphones enables remote surveillance and camera control in real-time from any location.
- Supports image snapshots and image forwarding via email and FTP upload.



XPY-530 Integrated wireless IP camera

www.nexxtsolutions.com

Minimum requirements

- Internet Explorer 5.5 or Firefox 1.0
- CD-ROM Drive
- Network adapter
- Internet access

Package content


- AILPT324U6 Integrated wireless IP camera
- Power adapter 110/220V
- Network cable
- Mounting bracket
- Quick installation guide
- CD-ROM

Software environment

System: 32 or 64 bit Windows2000/WindowsXP/
Windows2003/WindowsVista/Windows /7Mac OS.

Browser: Internet Explorer/Mozilla Firefox/Google Browser
TCP/IP network protocol

Viewing applications





XPY-530

Integrated wireless IP camera

www.nexxtsolutions.com

Model	AILPT324U6	
Specifications		
Camera	Image sensor	¼ -inch color CMOS
	Resolution	1280x720 (HD), 640x480 (VGA), 320x240 (QVGA),
	Lens	4mm
	Viewing angle	Horizontal 57° - Vertical 49.5°
	Minimum illumination	0 Lux
	Infrared LED	8 lights
	Night vision range	5m
	IR cut filter	Yes
	Digital zoom	Yes (with IPC Monitor software)
	Memory card slot	Yes (with micro-SD card)
	Dimensions	4.3 x 4.4 x 5 inches
Weight	0.75lb	
Video/ Image	Compression	H.264 and MPEG
	Frame rate	30 fps
	Mirror/Flip	Yes
	Record file format	PAL/NTSC
Audio	Communication	2-way
	Compression	G.711 and G.726
	Input	Built-in microphone
	Output	Built-in speaker plus I/O audio jacks
Network	Interface	RJ-45 (10/100)
	Supported protocols	TCP/UDP/IP/ARP/ICMP/DHCP/DNS/HTTP/FTP/SMTP/NTP/PPPOE/UPNP/DDNS
	Dynamic DNS	Yes
	Firewall security	No
	Port forwarding	No
Wireless	DHCP	Yes
	Standards	IEEE 802.11b/g/n
	Antennas	1 (detachable)
	Antenna gain	2dBi
Pan/Tilt	Network security	WEP, WPA-PSK and WPA2-PSK
	Range	Horizontal 350°, Vertical 100°
	Horizontal speed	0 - 16°/s
	Vertical speed	0 - 16°/s
Software	Features	Supports 8 preset positions
	Software setup	CD
Surveillance management	Parental control	Yes
	Remote management	Yes
	Multiple user management system	Yes
	Split screen view	Yes
	Web management for mobile devices	Yes
Alarm & notifications management	Mobile App	No
	Alarm ports	Yes
	Motion detection	Yes
	Notification method	Yes
Additional information	Notification scheduling	Yes
	Certifications	FCC
	Browser compatibility	IE 5.5 or above, Mozilla Firefox, Safari, Opera, Chrome
	Minimum system requirements	32 or 64 bit Windows, 2000/XP/2003/Vista/7/Mac OS
	Power	DC 5V
	Box dimensions	8.3 x 5.6 x 5.3 inches
	Box weight (WxHxL)	1.61lb
Warranty and technical support	One-year warranty, plus a two-year extension when the product is registered online	
UPC	798302033276	